

YUANWANG DEFOAMER YW-601L

PRODUCT DESCRIPTION

YW-601L is a fatty alcohol antifoam, which is recommended for use in papermaking.

FEATURES

- The substance components of the antifoam do not contain the substances listed in the SVHC list of the REACH Regulation.
- Antifoaming agent component does not contain NP, APEO.
- Application temperature range is between 25℃ to 40℃

COMPOSITION

- Composed of higher fatty alcohols and fatty acid derivatives.

TYPICAL PROPERTIES

Index	Result	Test Method
Appearance	White or slightly yellow uniform emulsion without sediment and visible mechanical impurities	Ocular Estimate
Nonvolatile Content (%)	29.0±1.0	GB/T 26257-2011
pH	6.0~8.0	pH meter test solution

Note: The information above is for reference and shall not be deemed as a technical indicator.

HOW TO USE

- YW-601L is a compound and it belongs to unstable thermodynamic. Probably this product stratifies or has deposits after long placed and it is normal phenomenon. Stir the product evenly at 30rpm to 60rpm before using and it does not affect the performance of product. The product cannot be placed exposure for a long time, or the product maybe crust and finally the viscosity of the product increases.
- this product can be used in on-line dilution with water directly. If it needs to be diluted before using, please dilute it according to the provided method. Please request the company's customer service department for the specific dilution method. The company accepts no responsibility for any loss which may be incurred by the customer as a result of incorrect usage. It is recommended to add 100ml-300ml/ton of paper on site.

● This product is easy to produce foam when it endures shear force. The antifoam should be added direct pumping and the product is added in the place where the antifoam is easy to disperse easily. (Note: The temperature of the addition point must be within the applicable temperature range of the product)

PACKAGE AND STORAGE

The product is available in 200-kg or 1000-kg plastic bucket. This product should be stored in cool and ventilated place. Don't near the heat source or sunlight. No exposure to rain. Keep away from flame. Don't add acid, alkali, salt and other corrosive substances to this product. Ensure the container is sealed after using. This product may freeze under 0°C (32°F); if this happens, stir well after defrosting the antifoam at a rate of 30 to 60 rpm. In these cases, stirring will not affect the performance of the product if carried out at the recommended speed. When stored between 10 and 30°C (50-86°F) in the original unopened containers, the product has a usable life of 6 months from the date of manufacture.

STANDARD: ZXBZ-2019

LIMITED WARRANTY INFORMATION

Please read carefully: The information contained herein is offered from experiences and knowledge in our company. The proposed application method of this product is for reference only. If it is not sure that the product is safe, effective, and fully satisfactory for the intended end use, please contact the dealer or YUANWANG directly. It is recommended that the customer conduct preliminary tests, ensuring product safety and effectiveness. Each customer has different system conditions.

Please get in contact with the YUANWANG Company if you are uncertain that your product is meeting guarantees. If the product is not in accordance with product standards, YUANWANG will assume liability and refund the payment of goods or replace the product. Our company can provide the SDS on request.